

# Watson LED Outdoor Sconce WTNW Series

#### **Features**

Simplistic design. Down light with wall wash effect. Ideal use in entrances or anywhere general outdoor lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

#### Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

#### **Finish**

All metal parts are powder coated in white or black.

#### Diffuser

Frosted white glass bottom diffuser.

#### **Electrical**

Input 120-277 VAC / 60 Hz. 0-10V dimming. Minimum starting temp -4° F/ -20°C.

### Lamping

Integrated LED modules capable of producing: 12W = 1100 source lumens, 675 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

#### Certification

All fixtures are cETLus listed for wet locations. ADA

Title 24/JA8 Compliant (outdoor only).

#### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	
















## Ordering Information:

White	Black	LED		Delivered Lumens	сст	Н	w	D
WTNW0506L30D2WH	WTNW0506L30D2BK	12\\/	1100	675	3000K	6"	5"	3-1/2"