

Knox LED Outdoor Sconce KNXW Series

Features

Modern angular design. Open bottom for wall wash effect. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are powder coated in white or bronze.

Diffuser

Frosted glass diffuser.

Electrical

This unit is direct wired with a constant current LED driver rated for 120-277V VAC input, 0-10V dimmable. Minimum starting temp -20°F.

Lamping

Fixture includes an LED module capable of producing: 12W = 1000 source lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cETLus listed for wet locations. ADA


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.







Ordering Information:

			Source				
	White	LED	Lumens	CCT	Н	W	D
KNXW061010L30D2BZ	KNXW061010L30D2WH	12W	1000	3000K	10"	6-1/4"	3-1/2"