Sustainable Solutions

Customer Service: 1-800-460-7019

www.fluidfaucets.com

Specifications

Metal construction for durability and reliability

SPECIFICATIONS

- Pressure balancing volume control with 2-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 5-function round shower head and 8" shower arm
- Oceanside tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1012B or F1012B-PEX or F1012B-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Vancouver Series **Shower Head and Tub Spout Trim Kit**

Model: F152305T

Includes: F1001T

Sleeve Tube and Cap FP801013 Diverter Sleeve Tube FP6023041 Vancouver Handle FP605752 Square Diverter Handle FP6001143-2PB Square Cover Plate 5 Function Shower Head FP20100

FP6027008 8" Shower Arm

Oceanside/Vancouver Tub Spout FP6023034











