

SPECIFICATIONS

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 3-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 3-function hand shower and slide rail with wall outlet
- 6" square shower head and 8" shower arm
- Quad tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1003B or F1003B-PEX or F1003B-PEX-W Or:
- Requires PB valve with sharing F1003B-SHARE or F1003B-SHARE-PEX or F1003B-SHARE-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Polished Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower Head 1.8 gpm @ 60 psig
- Hand Shower 1.8 gpm @ 60 psig
- Tub Spout 4.5 gpm @ 60 psig

Codes and Standards


- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

 Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

 2 Year Limited Warranty on all industrial, commercial and business applications.

5-(1/2"-14NPT) 5-(1/2"-14NPT) 5-(1/2"-14NPT) 4¹⁵16" [125mm] 4¹⁵16" [125mm]



fluid Quad Series Shower Head, Hand Shower and Tub Spout Trim Kit Model: F163027T

Includes:

www.fluidfaucets.com

Customer Service: 1-800-460-7019

F1001T Sleeve Tube and Cap Diverter Sleeve Tube FP801013 FP6001143-3PB Square Cover Plate Square Diverter Handle FP605752 FP6016041 Quad Handle Slide Rail with Wall Outlet FA803 FP40120 3 Function Hand Shower 60" Shower Hose FP6001006 FP6027008 8" Shower Arm

FP6000150 6" Square Shower Head FP6016034 Quad Tub Spout





