


Ball | 52 > Configure item number from attributes below.

	Finish	Blade Span	Blade Color	Light Option	Control Option
#BAL	-	-	-	-	-
	•	•	•	•	•
	GW Gloss White	52 52" Span	WH White	NL No Light	001 Fan Speed Only
	BA Brushed Aluminu	ım	AL Aluminum	652 20W LED	002 Fan & Light – 3 Wire
			MP Maple		003 Handheld Remote
					004 Fan & Light – 2 Wire
					005 Wall/Remote Combo



Specifications

- 153mm x 18mm AC motor with reverse switch on fan body
- Die cast aluminum construction
- 52" span, plywood blades
- Includes 6" and 16" down rods (longer options also available)
- Optional LED light: 20W, 90 CRI, 3000K, 1800 lumens (dimmable) behind opal glass diffuser; CA Title 24, JA8-2019 compliant
- Slope compatible up to 33°; adapter available for slopes up to 45°
- Designed by Ron Rezek
- ETL listed for dry and damp locations
- Weight: 16 lbs (7.3 kgs)

Performance Data

LOWEST SPEED

RPM: 70 CFM: 1,631 Watts: 10.64 CFM/W: 153

HIGHEST SPEED

RPM: 205 CFM: 4,998 Watts: 69.28 CFM/W: 72

Energy Guide Data

Average Energy Use 42 Watts

> Average Airflow 3,420 CFM

Yearly Energy Cost \$12

Average Efficiency 81 CFM/Watt

^{*} Energy Guide Data represents weighted averages of low speed and high speed performance, assuming typical use (excluding light). For more information, visit www.modernfan.com.

Ball | 52



FAN FINISHES



PLYWOOD BLADES

Plywood blades are constructed of furniture grade veneers, painted or stained as shown here. Natural variations may exist in woodgrains and finishes.



BALL FAN CONTROLS

Selection of a control option is made at time of order and incorporated into the fan item number (except #FC-009A and #FC-009B which are sold as accessory items).



#FC-001 **Fan Speed Only Control** (no light)

For a single AC fan, providing four speeds. Not intended for a fan with light. Note: Not compatible with remote control.

Handheld Remote RF Control

Designed for independent operation

a single AC fan or AC fan with LED

light, providing three speeds and full

Includes RF handset, receiver, battery

using only one circuit (two wires).

and comes with a wall mounting

bracket for handset.



Fan & Light Control-3 Wire

For a single AC fan with LED light. providing four speeds and dimming function. Requires three wires from switch location to fan. Note: Not compatible with remote control.



RF Control-2 Wire

Designed for independent operation of a single AC fan or AC fan with LED light, providing three speeds and full range dimming (or "on/off" switching), using only one circuit (two wires). Includes RF wall control (with master power switch), switch plate and receiver.



#FC-009A / #FC-009B **Multi-fan Speed Controls** for AC Fans

(no lights)

Sold as an accessory item, providing three speeds for multiple AC fans on a single switch leg. FC-009A for 2-3 fans FC-009B for 3-6 fans

Note: Not compatible with remote control. Control of fan lights must be accounted for separately with owner provided control on separate switch leg.

#FC-004-LED Fan & Light



#FC-003-LED

#FC-005-LED **Wall/Remote Combo** RF Control-2 Wire

Designed for independent operation of a single AC fan or AC fan with LED light, providing three speeds and full range dimming (or "on/ off" switching), using only one circuit (two wires). Includes RF handset, RF wall control (with master power switch), switch plate and receiver.



DOWN RODS

The Ball ships standard with 6" and 16" down rods. Use the following part numbers to order accessory down rods.

	Finis	Length			
#DRD	-		-		
	•		•		
	GW	Gloss White	12	12"	
	BA	Brushed Aluminum	24	24"	
			36	36"	
			48	48"	
			60	60"	
			72	72"	

SLOPE ADAPTER

The Ball will accommodate ceiling slopes up to 33 degrees. The #045 slope adapter can accommodate slopes exceeding 33 degrees and up to 45 degrees.

Finish

#045

GW Gloss White

Brushed Aluminum

The Modern Fan Co. tel 541-482-8545 toll free 888-588-3267 email info@modernfan.com website modernfan.com