

Description:

Unwind under the cooling breeze created by the clean, crisp blades of this ceiling fan. A central LED light covered by a white opal shade provides a perfect way to light a room without flooding the space with harsh light. Six metal blades attach to the fan's center column ready to create a serene retreat in whatever space it calls home.

Specifications:

- White Opal glass Bowl
- A central LED light covered by a white opal shade provides a perfect way to light a room without flooding the space with harsh light.
- Six metal blades attach to the fan's center column ready to create a serene retreat in whatever space it calls home.
- Unwind under the cooling breeze created by the clean, crisp blades of this ceiling fan.
- Ideal for any living room, great room, or bedroom.
- Perfect for modern or transitional settings.
- Measures 60-inch width by 18-9/16-inch height.
- Uses one LED module that is included (24w max).
- Remote control included.
- Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.2 in W., 2.125 in ht., 5.2 in depth
- 80 in of wire supplied

Performance:

Number of Modules	1
Input Power	24 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	2,000/83 (LM-82)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
Warranty	Limited Lifetime Warranty
Labels	cULus Damp Location Listed
	Meets California Title 24 JA8-2019
	DC motor

P250026-031-30



Dimensions:

Diameter: 60 in
Height: 18-9/16 in

White Opal glass Bowl
Width: 7 in
Height: 2-3/8 in

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$5

Cost Range of Similar Models (19" – 84")

• Based on 12 cents per kWh and 6.4 hours use per day
• Your cost depends on rates and use
• Energy Use: 19 Watts

Airflow

5,331

Cubic Feet Per Minute

• The higher the airflow, the more air the fan will move
• Airflow Efficiency: 282 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy



P250026-031-30

Dimming Notes:

P250026-031-30 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron	NTEVL-300
Lutron	DVELV-300P
Lutron	DVCL-253P
iDevices	IDEV009
Lutron	THCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.