


TUBE ARCHITECTURAL DS-CD05

LED Ceiling Mounts

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent lighting. Comes in various light beam angle options.

FEATURES

- High performance exterior rated LED ceiling light
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star® 2.0 rated (labeled with *)
- Operating Temp:** -13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter	Watt	Beam	Angle	Color	Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
DS-CD05	27W	S Spot	18°	927	2700K	90	1680	8526	62		BK Black WT White BZ Bronze GH Graphite
				27*	2700K	85	1800	9151	67		
				930	3000K	90	1700	8639	63		
				30*	3000K	85	1995	10126	74		
				35*	3500K	85	2190	11118	81		
				40*	4000K	85	2260	11483	84		
		N Narrow	25°	927	2700K	90	1730	5513	64		
				27*	2700K	85	1855	5918	69		
				930	3000K	90	1750	5587	65		
				30*	3000K	85	2055	6548	76		
				35*	3500K	85	2255	7190	84		
				40*	4000K	85	2330	7426	86		
		F Flood	33°	927	2700K	90	1725	4246	64		
				27*	2700K	85	1850	4557	69		
				930	3000K	90	1745	4302	65		
				30*	3000K	85	2045	5043	73		
				35*	3500K	85	2245	5537	83		
				40*	4000K	85	2320	5719	86		

DS-CD05- _____ - _____

Example: DS-CD05-N927-BK

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122


Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-CD06

LED Ceiling Mounts

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent lighting. Comes in various light beam angle options.

FEATURES

- High performance exterior rated LED ceiling light
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star® 2.0 rated (labeled with *)
- Operating Temp:** -13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color	Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
DS-CD06	36W	S Spot	16°	927	2700K	90	2420	15955	69		BK Black WT White BZ Bronze GH Graphite
				27*	2700K	85	3105	20455	89		
				930	3000K	90	2572	16977	74		
				30*	3000K	85	3195	21068	91		
				35*	3500K	85	3350	22091	96		
		40*	4000K	85	3385	22296	97				
		N Narrow	29°	927	2700K	90	2385	6872	68		
				27*	2700K	85	3055	8694	87		
				930	3000K	90	2535	7216	72		
				30*	3000K	85	3150	8955	90		
				35*	3500K	85	3300	9390	94		
		40*	4000K	85	3330	9477	95				
		F Flood	37°	927	2700K	90	2385	4859	68		
				27*	2700K	85	3060	6229	87		
				930	3000K	90	2540	5170	73		
30*	3000K			85	3150	6416	90				
35*	3500K			85	3305	6727	94				
40*	4000K	85	3335	6790	95						

DS-CD06-_____ - _____

Example: DS-CD06-N927-BK

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122


Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-CD08

LED Ceiling Mounts

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent lighting. Comes in various light beam angle options.

FEATURES

- High performance exterior rated LED ceiling light
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star® 2.0 rated (labeled with *)
- Operating Temp:** -13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter	Watt	Beam Angle	Color	Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
DS-CD08	48W	S Spot 18°	927	2700K	90	3075	11830	64		
			27*	2700K	85	3540	13616	74		
			930	3000K	90	2975	11443	62		
			30*	3000K	85	3615	13904	75		
			35*	3500K	85	3855	14822	80		
			40*	4000K	85	3915	15054	82		
	48W	N Narrow 21°	927	2700K	90	3075	16383	64		
			27*	2700K	85	3540	18857	74		
			930	3000K	90	2975	15847	62		
			30*	3000K	85	3615	19255	75		
			35*	3500K	85	3855	20526	80		
			40*	4000K	85	3915	20847	82		
	48W	F Flood 34°	927	2700K	90	3035	6200	63		
			27*	2700K	85	3495	7136	73		
			930	3000K	90	2935	5997	61		
			30*	3000K	85	3570	7287	74		
			35*	3500K	85	3805	7768	79		
			40*	4000K	85	3865	7890	81		

- BK** Black
- WT** White
- BZ** Bronze
- GH** Graphite

DS-CD08-_____-_____-_____

Example: DS-CD08-N927-BK

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760