

## ASSEMBLY AND INSTALLATION INSTRUCTION

**WARNING: SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER!**

**NOTE: BEFORE INSTALLING, CONSULT LOCAL ELECTRICAL CODES FOR WIRING AND GROUNDING REQUIREMENT.**

### Installation Steps:

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to lose any small parts necessary for installation.
2. Assemble the Threaded Nipple(A) onto the Cross Bar and lock it in place by hex nut. Attach the Cross Bar assembly to Outlet Box by using two Outlet Box Screws upwards. Secure the Screw Collar onto the other end of Threaded Nipple(A).
3. This fixture includes 3SET(21pcs) pipes to be connected into various height. Measure and determine correct number of Pipes required. Feed the wires from fixture and through Pipe, connect the Pipe to the Threaded Nipple(C) from Fixture Frame. Thread the Threaded Nipple to inside of each Pipes, connect all the pipes together until secure.
4. Slide fixture wires through Joint and Mounting Cover, lock them securely with the Hex Nut and Lock Washer. Slide fixture wires through Threaded Nipple(B), Cover and Fixture Loop, tighten with Fixture Loop and Finials.
5. Determine the length of Chain needed, using pliers to disconnect the unneeded Chain. Connect desired Chain length using Chain Links. Slide the Collar Ring through the Chain, put one Chain Link on the Fixture Loop and the other one on Screw Collar.
6. Weave the Fixture Wires including Ground Wire through Fixture Loop, every other Chain, Screw Collar, Collar Ring, Canopy and Threaded Nipple(A) on the Cross Bar.
7. Using a Wire Nut, connect the White Fixture Wire to the White Supply Wire, connect the Black Fixture Wire to the Black Supply Wire, connect Fixture Ground Wire to Supply Ground Wire, or attach Fixture Ground Wire to the Cross Bar with a green ground screw. Make sure all Wire Connectors are secure and do not easily pull off with the slight tug.
8. After the wires connected, raise Canopy against ceiling and tighten with Collar Ring.
9. Install the light bulbs(Not included) in accordance with the fixture's specifications.  
**NOTE: DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
10. Your installation is now complete. Return the power to the Outlet Box and test the fixture.

